

DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) NR. 305/2011
Amended by Commission Delegated Regulation (EU) Nr. 574/2014

No: EH0074-13-10-2020

Unique identification code of the product type:
CUGLA Paving Plast 2525 con.15% PL

Intended use/s:
Water reducing/plasticizing admixture - EN 934-2: T2

Manufacturer
Cugla BV
Rudonk 11
4824 AJ BREDA

System/s of AVCP
System 2+

Harmonised standaard
EN 934-2:2009+A1:2012

Notified body/ies
KIWA Nederland BV 0956

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Chloride ion content	max. < 0,1 % (m/m)	System 2+	EN 934-2:2009 + A1:2012
Alkali content	max. 1% (m/m)		
Corrosion behavior	Contains components only from EN 934-1: 2008, Annex A.1		
Compressive strength	At 7 days Test mix \geq 110 % control mix At 28 days: Test mix \geq 110 % control mix		
Air content	Test mix \leq 2 % by volume above control mix		
Air content (entrained air)	NPD		
Air void characteristic	NPD		
Water reduction	Test mix \geq 5 % compared with control mix		
Bleeding	NPD		
Setting time	NPD		
Hardening time/strength development	NPD		
Capillary absorption	NPD		
Consistency	NPD		
Dangerous substance	NPD		
Durability	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

H.J. Dikmans
Technical director
(name)

Breda, 28-11-2019
(place and date of issue)



(signature)

Annex

According to Art. 6() of the Regulation (EU) No. 305/2011 a Safety Data Sheet according to Regulation (EU) No. 1907/2006 (REACH), Annex II, is attached to this Declaration of Performance.

Cugla BV
Versie: 28-11-2019