

## CUGLA® PAVING PLAST 1400 CON.15% SPL

Admixture in accordance with NEN-EN 934-2.



0956-CPR-1501

CUGLA PAVING PLAST 1400 is ideal for producing high quality plain concrete and pouring complex concrete constructions.

### User advantages

<b>Workability</b>	Ready-mixed concrete with a low water-cement ratio can be processed as liquid concrete, allowing complex formwork with dense reinforcement to be filled.
<b>Strength</b>	The low water-cement ratio achieves high initial strengths and high final strengths.
<b>Durability</b>	The concrete's highly dense structure increases the sustainability.
<b>Reduced cement requirement</b>	Target strengths can be achieved with substantially reduced cement requirements.
<b>Compaction</b>	The high workability requires minimal compaction for optimum density.
<b>Formwork removal</b>	The high initial strength enables a faster formwork removal, allowing concrete shuttering to be more effectively used.

### Product properties

<b>Product name</b>	CUGLA PAVING PLAST 1400	
<b>Category</b>	Super plasticiser	
<b>Manufacturer / Supplier</b>	CUGLA	
<b>Colour code</b>	Grey	
<b>Aggregation state</b>	Fluid	
<b>Colour</b>	Brown	
<b>Soluble in water</b>	Yes	
<b>Concentration</b>	%	15
<b>pH</b>		2 - 8
<b>Unit mass</b>	kg/l	1,03 ± 0,02
<b>Solid</b>	%	15 ± 1,5
<b>Total chloride content</b>	%	< 0,1
<b>Water soluble chloride</b>	%	< 0,1
<b>Alkali content</b>	%	1,0

## Application and dosing instructions

<b>Manner / time of dosage</b>	Preferably, add to the last measure of mixing water		
<b>Recommended dosage</b>	Depending on the desired consistency range of the concrete		
<b>Application temperature</b>	5 - 30 °C		
<b>Storage and storage life</b>	One year in sealed package at a minimum temperature of 5 °C		
<b>Suitable for use in</b>	Mass concrete Reinforced concrete Pre-stressed concrete		
<b>Not combinable with</b>	Aluminium cement: only in consultation with Cugla Other admixtures: only in consultation with Cugla		
<b>Admixture concentration</b>	<b>%</b>	15	
<b>Maximum dosage</b>	<b>% in relation to weight of cement</b>	3,5	
	<b>cc per 100 kg cement</b>	3400	
For dosing higher than the maximum recommended dosage, please contact the Product Manager of Cugla for advice			

## Packaging

Packaging in cans, barrels, containers and/or bulk

## Health and environmental aspects

Cugla recommends that when using Cugla admixtures:

- Should the product come in contact with eyes, rinse immediately with water and seek medical advice.
- Should the product come in contact with skin, wash immediately with soap and water.
- Should you feel ill, consult a doctor, showing him/her this sheet or the safety information sheet

**For detailed information we refer to the safety data sheet, SDS Cugla Paving Plast 1400 con.15% SPL, on our website.**

Changes to this documentation are not sent to customers automatically. All previous product information hereby lapses. The above values concern laboratory conditions and are provided to the best of our knowledge. We cannot accept any liability for results obtained on site because we are not responsible for product processing or the specific conditions on site.

Our general terms and conditions of sale, supply and payment apply to all our transactions (see [www.cugla.com](http://www.cugla.com)).