

Cuglacrete Hechtprimer epoxy sealer

- CUGLACRETE HECHTPRIMER EPOXY SEALER is a solvent-free 2 component system, consisting of:
Component A: epoxy resin
Component B: modified polyamineharder
- CUGLACRETE HECHTPRIMER EPOXY SEALER is an excellent bonding primer for the CUGLACRETE concrete repair products.

Directions for use

Pre-treatment

The surface onto which CUGLACRETE HECHTPRIMER EPOXY SEALER has to be applied needs to be clean. The cement skin coating should be removed and no free water may be present.

Mixing

Add component B to component A, then mix until a homogenous mixture. Afterwards pour into another can and again mix to prevent incomplete hardening or soft areas.

Processing

After using CUGLACRETE HECHTPRIMER EPOXY SEALER, the CUGLACRETE repair product needs to be applied "wet in wet".

Potlife

Approx.: 40 minutes

Use

Approx. 0,25 kg dry material per m².

Cleaning

Clean utensils with CUGLA EPOXY HARSREINIGER before CUGLACRETE HECHTPRIMER EPOXY SEALER begins to harden.

Follow-up treatment

Not applicable

Storage and shelf life

If stored in a dry place it has a shelf life of up to 12 months after production date, as stated on the packaging.

Packaging

Set of 0,25kg and 1,0kg.

Health and environmental aspects

Cugla advises:

- To wear appropriate personal protective equipment (PPE),
- to apply the product in well ventilated areas,
- to wear suitable protective clothing, gloves and safety goggles,
- to avoid contact with eyes and skin,
- in case of contact with eyes, rinse immediately with plenty of water and seek medical advice,
- in case of contact with skin, rinse immediately with plenty of soap and water.

Safety data sheets, SDS, are available via our website www.cugla.com.